



PRIMO PX no.2 / the Sequel



PRIMO PX no.2 / the Sequel



SPECIFICATIONS PRIMO PX no.3 / the Addition

- Compatible with PRIMO PX no.2 / the Sequel
- Possibility to place 5th base feet centered in tile
- No transit caps

Tile:

Synthetic Polycarbonate / Black

500 x 500 x 40 mm (19.68 x 19.68 x 1.57 inch)

Antistatic

Flame retardant

Transit cap: \varnothing 130 mm (5 inch)

No transit caps

Weight: 4,3 kg per tile / 17,2 Kg per m² (9,5 Lbs per tile / 38 Lbs per 10,8 ft²)

Base feet (same as PRIMO no. 2):

Synthetic ABS

66 x 66 x 90 mm (2.59 x 2.59 x 3.5 inch)

Colour: black

Antistatic

weight 0,15 kg

Flame retardant

Galvanized steel adjustment screws with Allen wrench with ball-end 6 mm

Minimum height 90 mm or 3.54 inch (included height tile)

Maximum height 165 mm or 6.5 inch (included height tile)

Pass through under flooring level 50 – 120 mm (1,96 – 4,72 inch)

Loading capacity

Static load: 1000 kg per 1 m² (205 Lbs per ft²)

Dynamic load: 200 kg per 1 m² (41 Lbs per ft²)